

<b>Models</b>	<b>HITACHI EX 2600-6 BE</b>
<b>Driveline</b>	
Emission Rating	Tier 2
Number Of Cylinders - Per Engine	16
Displacement	50 ltr / 3051 Inches <sup>3</sup>
Rated Speed	1800 rpm
Engine Output Per Engine- Net	1069 kW / 1434 hp
Carrier Rollers - Each Side	3
Track Rollers - Each Side	8
Track Shoe Width	1000 mm / 39 inches
<b>Dimensions</b>	
Transport Length	10225 mm / 33 ft 7 in ft/in
Transport Height - Maximum	7250 mm / 23 ft 9 in ft/in
Overall Width	8040 mm / 26 ft 5 in ft/in
Track Length On Ground	6120 mm / 20 ft 1 in ft/in
Undercarriage Overall Length	7870 mm / 25 ft 10 in ft/in
Tailswing Radius	6290 mm / 20 ft 8 in ft/in
Ground Clearance	800 mm / 31 inches
Width over standard tracks	6000 mm / 19 ft 8 in ft/in
Track Gauge	5000 mm / 16 ft 5 in ft/in
Dig height (mono)	15800 mm / 51 ft 10 in ft/in
Dump Height (Mono)	10100 mm / 33 ft 2 in ft/in
Max Digging Reach (Mono)	16600 mm / 54 ft 6 in ft/in
Ground level reach (mono)	16050 mm / 52 ft 8 in ft/in
Dig depth - 2.44m / 8'ft flat bottom	8150 mm / 26 ft 9 in ft/in
Dig depth (mono)	8250 mm / 27 ft 1 in ft/in
<b>Capacities</b>	
Fuel Tank	5300 ltr / 1400 gallons (US)
Hydraulic Tank	1320 ltr / 349 gallons (US)
<b>Performance</b>	
Ground Bearing Pressure	185 kPa / 26.8 PSI
Dipper Tearout	785 kN / 176475 lbf
<b>Weights</b>	
Weight - Maximum	254000 kg / 560000 lbs