



H30FT HIGHLIFT SHEETS



CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
 EQUIPPED WITH 42" FORKS & STANDARD CUSHION TIRES
 SIDESHIFT RATINGS WITH INTEGRAL SIDESHIFTER

		MFH	OALH	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
				CARRIAGE	SIDESHIFT	LIFT HEIGHT	CARRIAGE	LIFT HEIGHT	SIDESHIFT
H30FT Standard Tread	2stg LFL 5 Deg Back Tilt	107.0	74.0	3000	2900	107.0	3000	107.0	2900
		111.0	76.0	3000	2900	111.0	3000	111.0	2900
		115.0	78.0	3000	2900	115.0	3000	115.0	2900
		119.0	80.0	3000	2900	119.0	3000	119.0	2900
		123.0	82.0	3000	2900	123.0	3000	123.0	2900
		127.0	84.0	3000	2900	127.0	3000	127.0	2900
		190.0	120.0	2700	2700	164.0	3000	164.0	2850
	2stg FFL 5 Deg Back Tilt	107.0	74.0	3000	2900	107.0	3000	107.0	2900
		111.0	76.0	3000	2900	111.0	3000	111.0	2900
		114.0	78.0	3000	2900	114.0	3000	114.0	2900
		118.0	80.0	3000	2900	118.0	3000	118.0	2900
		122.0	82.0	3000	2900	122.0	3000	122.0	2900
		126.0	84.0	3000	2900	126.0	3000	126.0	2900
	3stg FFL 5 Deg Back Tilt	190.0	118.0	2650	2650	164.0	3000	164.0	2800
		151.0	72.0	3000*	2850	151.0	3000	151.0	2850
		175.0	80.0	2600	2600	164.0	3000	164.0	2850
		187.0	84.0	2200	2200	164.0	3000	164.0	2850
		192.0	86.0	2050	2000	164.0	3000	164.0	2800
		198.0	90.0	1900	1850	164.0	3000	164.0	2800
		216.0	96.0	1450	1400	164.0	2950	164.0	2800
		234.0	104.0	1050	1000	164.0	2950	164.0	2800
251.0	112.0	750	650	164.0	2950	164.0	2750		
H30FT Wide Tread	3stg FFL 5 Deg Back Tilt	175.0	80.0	2950	2800	164.0	3000	164.0	2850
		187.0	84.0	2850	2700	164.0	3000	164.0	2850
		192.0	86.0	2800	2650	164.0	3000	164.0	2800
		198.0	90.0	2650	2600	164.0	3000	164.0	2800
		216.0	96.0	2150	2150	164.0	2950	164.0	2800
		234.0	104.0	1750	1700	164.0	2950	164.0	2800
		251.0	112.0	1350	1350	164.0	2950	164.0	2750

Version V9.01 beta (05/2005)

*Highest Non-High Lift Mast Rated at Full Capacity
 Wide Tread listed for Lift Heights where capacity is dependant on Tread Width.

Actual mast dimensions may vary slightly from nominal dimensions stated in price book. The designed Overall Lowered Height (OALH) is stated to the next higher full inch, and Maximum Fork Height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances.

For capacity estimates for other truck configurations or for trucks with attachments, consult your copy of the Hyster HY-Rater truck rating software. Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834