



H40FT HIGHLIFT SHEETS



CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
 EQUIPPED WITH 42" FORKS & STANDARD PNEUMATIC TIRES
 SIDESHIFT RATINGS WITH INTEGRAL SIDESHIFTER

		MFH	OALH	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY				
				CARRIAGE	SIDESHIFT	LIFT HEIGHT	CARRIAGE	LIFT HEIGHT	SIDESHIFT	
H40FT Standard Tread	2stg LFL 6 Deg Back Tilt	121.0	82.0	4000	3950	121.0	4000	121.0	3950	
		129.0	86.0	4000	3950	129.0	4000	129.0	3950	
		149.0	96.0	4000	3950	149.0	4000	149.0	3950	
		170.0	109.0	4000	3900	170.0	4000	170.0	3900	
	2stg FFL 6 Deg Back Tilt	122.0	82.0	4000	3950	122.0	4000	122.0	3950	
		130.0	86.0	4000	3950	130.0	4000	130.0	3950	
		149.0	96.0	4000	3950	150.0	4000	150.0	3950	
	3stg FFL 6 Deg Back Tilt	171.0*	78.0	4000	3850	171.0	4000	171.0	3850	
		189.0	84.0	3850	3700	171.0	4000	171.0	3850	
		194.0	86.0	3650	3650	171.0	4000	171.0	3850	
		200.0	90.0	3450	3450	171.0	4000	171.0	3850	
		218.0	96.0	2900	2850	171.0	4000	171.0	3800	
		224.0	100.0	2750	2700	171.0	4000	171.0	3800	
		230.0	102.0	2550	2500	171.0	3950	171.0	3800	
H40FT Wide Tread	3stg FFL 6 Deg Back Tilt	171.0	78.0	4000	3850	171.0	4000	171.0	3850	
		189.0	84.0	3850	3700	171.0	4000	171.0	3850	
		194.0	86.0	3800	3650	171.0	4000	171.0	3850	
		200.0	90.0	3700	3600	171.0	4000	171.0	3850	
		218.0	96.0	3500	3400	171.0	4000	171.0	3800	
		224.0	100.0	3450	3300	171.0	4000	171.0	3800	
		230.0	102.0	3350	3200	171.0	3950	171.0	3800	
	4stg FFL	228.0	84.0	Contact Applications Engineering						
		240.0	87.0							
		252.0	91.0							
264.0		95.0								

* Highest Non-High Lift Mast Rated at Full Capacity

Wide Tread listed for Lift Heights where capacity is dependant on Tread Width.
 Wide Tread is required with 4-Stage FFL Mast.

Actual mast dimensions may vary slightly from nominal dimensions stated in price book. The designed Overall Lowered Height (OALH) is stated to the next higher full inch, and Maximum Fork Height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances.

For capacity estimates for other truck configurations or for trucks with attachments, consult your copy of the Hyster HY-Rater truck rating software.
 Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834